The Access 2000 Modular control panel is an autostart control system used to provide remote starting capabilities for FG Wilson generating sets. It has been designed to meet the demands and practices of today's marketplace. The panel delivers a high value package while setting the standard in reliability, serviceability and package integration. Based on a modular concept, with a choice of snap-fit engine control and AC metering modules, the panels can easily be upgraded or replaced. Modules can be calibrated on site.



# Access 2000



## **Standard specification**

- Microprocessor controlled
- Engine parameter monitoring
- Spare fault channel for optional shutdowns or alarm
- Digital display of current, voltage and frequency
- Autostart
- Sheet steel cabinet
- Excellent cable access
- Membrane keypad with tactile feedback
- UV stabilised IP55 fascia, impervious to diesel fuel or lubricating oil
- ► Wide operating temperature (-10 deg to +70 deg C)

# Modular Control panel



### **Standard features**

### AC metering

AC voltage AC current Frequency (Hz)

## Controls

Ready/off/reset push button Cold weather start Start push button

#### Shutdowns

Low oil pressure (integrated into oil pressure gauge) High water temperature (integrated into water temperature gauge) Overspeed/emergency stop Fail to start/lockout

#### Alarms

Charging alternator failure (integrated into battery voltmeter) Glow plugs energised

#### Status indicators

System activated (heartbeat) Hours run meter Battery voltmeter Oil pressure gauge Water temperature gauge

#### Spare warning/Shutdown fault

One additional fault channel available, programmable for shutdown or alarm

## **Optional features**

- 4 pole breaker
- Earth leakage trip
- High lube oil temperature shutdown\*<sup>†</sup>
- Low fuel level shutdown\*
- ► 5A battery charger
- Coolant heater
- \* Only 1 may be chosen, <sup>†</sup> Not available on 3 cylinder models

- ► Volt free contacts for common alarm
- Low fuel level alarm\*
- High fuel level alarm\*
- Low coolant temperature alarm\*
- Low coolant level shutdown

## Standards

- 98/37/EC Machinery directive
  BS EN 60204 1 Safety of machinery
- 89/336/EEC EMC directive: amended by 91/368/EEC, 93/44/EEC, 93/68/EEC
   BS EN 50081 - 1 Emissions standard
   BS EN 50082 - 2 Immunity standard
- 73/23/EEC Low voltage directive: amended by 93/68/EEC
   EN 50178 LVD standard



FG Wilson (Engineering) Ltd Old Glenarm Road, Larne, County Antrim BT40 1EJ Northern Ireland, United Kingdom Tel: +44 (0) 28 2826 1000 Fax: +44 (0) 28 2826 1111 www.FGWilson.com

